



LC87306

TECHNICAL DATA SHEET


LED NEON FLEX



DIMENSIONS (MM)



PRODUCT NUMBER	LC87306
MAXIMUM LENGTH	5,000 MM
INPUT VOLTAGE	12VDC OR 24VDC
POWER CONSUMPTION	MAX 16W PER M (SINGLE CCT)
LED SOURCE	EPISTAR 2835 SMD (>80RA)
	SAMSUNG 2835 SMD (>90RA)
CONTROL METHOD	ON/OFF, 0-10V, DALI, DMX
MATERIAL	SILICON
OPTICS	115°
BEND RANGE (LATERAL BENDING)	60MM
OPERATING TEMPERATURE	-25 TO 45°C
LED STRIP/RIGID (ORDER SEPARATELY)	UP TO 8 MM WIDE
LUMEN PER METER	MAX. 950LM/M
IP RATED	IP20 / IP65 / IP67



ENDCAPS POWER FEED
ENDCAP CLOSED



INSTALLATION CLIPS

CONFIGURE THIS PRODUCT

SERIES	VOLTAGE	IP RATING	LENGTH	ENDCAP POWER ENTRY
LC87306	DC 12V	IP20 20	1000 MM	END
	DC 24V	IP65 65	2000 MM	
		IP67 67	3000 MM	
			4000 MM	
			5000 MM	
			CUSTOM CUS	